



## NETRA CCTV HD-IP SERIES CAMERA

### NR-UV20-HD/NR-UV20-HD-IR/NR-UV20-HD-IR/LS series HD IP high speed Pan Tilt camera

High Definition, High Performance, Wide Angle

#### Main feature

##### Pan tilt feature :

- Step motor driving, providing accurate position and quick response
- Manual speed: 0.1°-80°/sec for pan; 0.1°-40°/sec for tilt
- Preset speed: 80°/sec for pan; 40°/sec for tilt
- changeable auto-touring speed can be set from 1°-40°/sec



##### Camera feature:

- Built in high definition integrated zoom camera
- BLC
- Day/Night image
- WDR

##### build-in decoder feature:

- Build-in OSD menu, camera, pan tilt function can be set
- 255 preset position, error less than ± 0.10
- Auto flip function
- Change speed proportionally-pan/tilt speed and the depth of zoom lens decline proportionally
- Support setting virtual zero position
- Auto pan scanning function
- One pattern of 4 preset touring function and 32 presets for each pattern.
- Power off memory: the movement before power off can be memorize
- Click to large function

- Support Dual stream video encoding, fully meeting the different bandwidth of network in actual application.
- Support character and video superposition displaying.
- Built in Web Server, support browser preview, configure and update.
- Support two-way talking
- Support video timing, alarm linkage snapping , images can be stored directly, sent by Email or uploaded by FTP by default JPG format
- Support static address DHCP.
- Equipped with Client software.
- Support central platform software management
- Support multipile network protocols TCP/IP, UDP, SMTP, PPPoE, DDNS, DNS , UPNP , DHCP, FTP ,RTSP etc.
- Meeting ONVIF standard
- Support 1 ways alarm input and 1 AUX
- Support maximum up to 32GB of TF card storage. Video can be stored locally when there is network failure. The storage will adopt the re-distributed file system and prevented the disk fragments which eliminate the worry of black out

##### Network feature

- high performance video processing chip and H.264 video coding, providing standard H.264 video compress format.
- Standard G.711 Audio compress format.
- Support 1080P、720P、D1、VGA formats.
- Support PAL.NTSC.

##### Protection feature

- with surge and lightning protector
- with wiper, heater, fans
- IP66, CE, FCC, ROHS compliance




## NETRA CCTV HD-IP SERIES CAMERA


### Order Model No

NR-UV20-HD-S  
 NR-UV20-HD-G wall mount  
 NR-UV20-HD-IR-S pedestal mount  
 with IR  
 NR-UV20-HD-IR-G wall mount with IR  
 NR-UV20-HD-LS-S pedestal mount with laser  
 NR-UV20-HD-LS-G wall mount with laser



### Dimension



### UV20-HD-LS



### UV20-HD-IR



### Technical parameters

Model	NR-UV20-HD	NR-UV20-HD-IR	NR-UV20-HD-LS
<b>Camera/Lens</b>			
Image sensor	1/3 HD CCD	1/2.8 inch HD CMOS	
scan system	progressive	progressive	
pixel	1.3 million	2 million	
Focal length	f=4.7-84.6mm	f=4.7-94mm	
angle	3.2° ( far ) ~ 55.2° ( near )	2.9° ( far ) ~ 55.4° ( near )	
zoom	18x optical /12x digital	20x optical/12x digital	
Zoom speed	5.2 sec	4.9 sec	
focus	Auto/manual	Auto/manual	
Len Iris	F1.6 ~ F36.2	F1.6 ~ F3.5	
Iris control	Auto/manual	Auto/manual	
Low lux	1.8lux 1/30s IrcfON 0.5lux 1/4s IrcfON 0.02lux 1/4s IrcfOFF	0.095lux 1/30s IrcfON 0.005lux 1/4s IrcfON 0.26lux 1/4s IrcfOFF	
shutter speed	Auto/manual	Auto/manual	
gain control	Auto/manual	Auto/manual	
White balance	Auto/manual	Auto/manual	
BLC	Open/off	Open/off	
Day/night	YES	YES	
WDR	YES	YES	
S/N	>50DB	>50DB	
<b>IR parameter</b>			
IR distance	None	IR	LASER
angle	None	100m	200m
IR lamps	None	18°	16°
voltage	None	2pcs	2
power	None	DC12V	DC12V
dimention ( LxWxH )	None	2*Φ108x85mm	215x92x112mm ( 2 pcs )
Net weight	None	2*0.5kg	2*0.5kg
<b>Video coding</b>			
format	H.264 Main Profile, MJPEG Baseline Encoding		
resolution	Main stream 720p ( 1280x720),sub stream MJPEG ( 640x352), support dual stream	Main stream 1080p ( 1920x1080 ), sub stream D1 ( 740x480), support dual stream	
Video code rate	64Kbps ~ 12Mbps	64Kbps ~ 12Mbps	
Video frame bitrate	1 ~ 30 frame/sec	1 ~ 30 frame/sec	
Title OSD	Supports channel name, date, and video stream information overlay	Supports channel name, date, and video stream information overlay	



## NETRA CCTV HD-IP SERIES CAMERA

Image adjust	brightness , contrast , saturation	brightness , contrast , saturation
<b>Outside interface</b>		
Web interface	1x10Base-T/100Base-TX , RJ45interface	
Alarm interface	1xswitch In , 1x switch Out	
Storage interface	1xTF card interface , build-in	
Audio interface	1x line in , 1xline output	
network protocol and feature		
protocol	TCP/IP , FTP , NTP , DNS , DDNS , SMTP , PPPoE, RTSP , ONVIF,28181	
<b>Application</b>		
Application	alarm linkage, voice monitoring and talkback	
Setting and maintenance	1 ) support web browser configuration management and video browse	
	2 ) can connect to platform(NVR) for parameter configuration and status management	
System integration support	offer fully functional API, SDK developer file	
<b>Electrical parameter</b>		
Input voltage	24VAC	
Input power	50VA ( UV20-HD ) ; 75VA ( UV20-HD-IR , UV20-HD-JL )	
Working temperature	-40°C ~ +55°C	
Working humidity	10%-90%	
<b>Structural</b>		
Material	Aluminum Alloy	
Glass	4.5mm high intensity optical coated glass	
Weight	11KG(UV20-HD) ; 12KG(UV20-HD -IR) ; 12KG(UV20-HD -LS) ( only for PTZ body )	
Color	Grey	
Body Dimension	200x355x460 mm ( UV20-HD ) ; 388x355x460 mm(UV20-HD-IR) ; 303x355x460mm (UV20-HD-LS)	
Package size	670mmx530mmx318 mm ( UV20-HD ), 638mmX468mmX482mm(UV20-HD-IR) (UV20-HD-LS)	
Package material	Carton+ Pearl cotton	
Mounting brackets	UV-EM20、UV-CM-A、UV-SM-A、UV-PM-A,UV-BM20 )	
Accessories	Manual(x1), Warranty card(x1), Certification(x1), Bracket (Optional), Power Supply(Optional), pedestal bracket(Optional), Φ8X40 bolt(x4), Gloves(x1), hydrosphere(x1), 13 Allen key(x1)	
Environment		
Working temperature	-40°C ~ +55°C; without IR : -25°C~+55°C , with IR : -10°C~+40°C:	
Storage Temperature	-10°~ 60°	
Working Humidity	20%~ 90%	
Storage Humidity	20%~ 80%	
Application	Outdoor, Indoor	
Transportation	Unlimited	
Grade of Protection	IP66(Outdoor), Built-in surge and lightning protection devices	
Cerftication	Meets CE, FCC standards and has ROHS certification	
Wiper	yes	
Defroster	yes	